

Model 2800-2805

Ceiling motor

Efficient and fast



- The fastest track motor
- Suitable for intensive use
- Featherlight sideways movement
- To be used with slings and/or the Handi-Move® Body Support
- To be used with classic spreader bar or electric tilting spreader bar
- Motor and rail systems make it possible to access all areas
- Wireless control optional
- Back-up control on motor
- Emergency down and stop within reach

Lift & Care systems for people with reduced mobility


www.handimove.com

Ceiling motor

● Technical specifications

Safe working load	200 kg/300 kg (3000 mm motorband: 160 kg)
Batteries	2 x 12 V 9.5 Ah/ rechargeable
Standard motor band length	2000 mm (option: 3000 mm)
Rail System	aluminium, lacquered in white
Smooth stop and go	electronic
Cover	ABS
Emergency down	mechanical
Handcontrol 2800	watertight IP67 electric
Handcontrol 2805	infra-red
Number of lifts with fully charged batteries	160
Load and battery indications	visual and auditive
Charger	input 0.9 A 100-240 Vac, 50-60 Hz Class II
.....	output 24 Vdc Max 1.3 A (9940) Max 1.2 A (2541)

● Examples of routes



● Versions*

2800

Lifting motor (up/down)

With electric handcontrol

2805 IR

Lifting motor (up/down)

With infra-red remote control

* also available with lateral motor (2810 L - 2815 L IR)




37 Chertsey Road, Chobham, Surrey, GU24 8PD

Tel: 01276 856060 Fax : 01276 858689 E: sales@dolphinlifts.co.uk

© 30-09-2015 • Handi-Move • v1.0

For free demonstration or further information



Handi-Move nv

Ten Beukenboom 13, B-9400 Ninove • Tel. +32 54 31 97 10 • Fax +32 54 32 58 27

info@handimove.com • www.handimove.com