



Wessex Homelift



Independence
in your
home

 **Wessex**
SPECIALISTS IN LOW RISE LIFTING SOLUTIONS
MEMBER OF THE RATCLIFF GROUP

Design Designed for safety, flexibility and total freedom and independence.

Unobtrusive Simple and unobtrusive, the Wessex Homelift's space saving design uses the absolute minimum of space in your home.

Solution The complete solution:

- Site survey by Wessex Area Sales Manager
- Completion of all electrical and building work
- Installation of lift by Wessex trained personnel
- Commission and demonstrate to client
- After sales care - service and maintenance

Peace of Mind Wessex fully trained engineers are regionally located at six depots throughout mainland UK. For that total assurance Wessex engineers are on call 24 hours a day 365 days a year.

Customer Care Contact our dedicated friendly team of people, experienced in offering a high level of customer care and individual attention. Our team can offer advice on everything from feasibility to installation and after care, together with an unparalleled level of technical support.
Contact them on: 01794 830303.



Standard Specifications

		VM30	VM31	VM36	VM50	VM51	VM56
Standard Seated Lifts		√	-	-	√	-	-
Standard Wheelchair Lifts		-	√	-	-	√	-
Large Wheelchair Lifts		-	-	√	-	-	√
3m Maximum Travel		√	√	√	-	-	-
3.5m Maximum Travel		-	-	-	√	√	√
Internal width	A	590	740	790	590	740	790
Internal length - Manual Door	B	790	1180	1230	790	1180	1230
Internal Length - Power Door	B	N/A	1150	1200	N/A	1150	1200
Total external length with door open to wall	C	1655	2190	2290	1655	2190	2290
Total external width including floating platform	D	722	872	922	722	872	922
Total external length including floating platform to wall	E	1090	1475	1525	1090	1475	1525
Minimum shaft width		846	996	1046	846	996	1046
Minimum shaft length		1120	1505	1555	1120	1505	1555
Minimum first-floor ceiling height		2040		2280			
Mid-floor dimensions		from 165mm to 300mm					
Safe working load		225kg					
Lift speed		60mm per second					
Ramp gradient		1.8					
Door adjustment		up to 95 degrees					
Car control illumination		4 - 20 minute duration					





