

Splash! Specifications

Technical:

- * **Lifting Capacity:** 300 lbs. or 400 (heavy duty model)
- * **Lifting:** Linak LA32 Mechanical Actuator
- * **Maximum Thrust:** 1680 lbs.
- * **Voltage:** 24 VDC
- * **Max. Amp:** 9
- * **Max Speed:** 0.59 inches/sec
- * **Rotation:** ITT SWMK 403.033 24 VDC 13 RPM
- * **Gearing Ratio:** 9:1
- * **Power:** Linak Rechargeable Batter Pack BAJ1
- * 24 VDC, IP65 Gel Lead Acid

Materials and Finish:

- * **Base:** Powder Coated Stainless Steel
- * **Housing:** Powder Coating Aluminum
- * **Mast:** Powder Coated, Zinc Plated Steel

Dimensions:

- * **Base Dimensions:** 18" diameter
- * **Total Weight:** 140 lbs.
- * **Overall Height:** 73"
- * **Overall Length (footprint):** 70-76" (fully extended); 53" stored position

Range of Motion:

- * **Lifting:**
 - Variable to suit needs of pool
 - 44 inches total travel with standard actuator
 - Seat depth 18-20" below waterlink
- * **Rotational:** 359 degrees total rotation