

Fixed Ceiling Lift V10

With a growing rate of obesity within the population... the risk of caregiver lifting related back injury has never been greater!

It's the solution you have been looking for to ensure the safe and dignified transfer of your nonambulatory bariatric patients. The V10 is a fixed ceiling lift that offers a lifting capacity of : 1000 lb (455 kg)



# Product	Description	Market	
9120001	V10 - 4 Directions	North America	
9120008	V10 - 4 Directions	Europe & United Kingdom	
5		F	8
# Part	Description	9120001	9120008
1 700.13650	Hand Control - 4 Way	•	•
2 700-15501	Charging Station	•	•

3 700.05570 4-point Spreader Bar

64 cm (251/4

66 cm (26")

Suggested Slings / Harness / Stretchers

Total support/ Semi-reclined position		Partial support/ Stand position	
	Hammock /Hammonk 6	Band	
	Quick Fit	Walking	
	Hygienic	Total transfer	
	Combi	Chest	
\checkmark	Bariatric		
Total support/ Lay-down position		Partial support/ Lay-down position	
\checkmark	Universal stretcher	Repositioning	
\checkmark	Morgue	Limb sling	

1

i.j

2

34 cm (13")

BIHM MEDICAL

Features				
Weight	22 kg (48 lb)			
Lifting capacity	455 kg / 1000 lb			
Soft start & stop movement				
Return to charge function on handset				
Safety Features				
Emergency lowering device	Manual & electric			
Device for emergency stop of the mechanism	Helps to prevent freefalls			
Emergency Stop Pull Cord				
Technical Specifications				
UL STD 2601-1 / ISO 10535 / CSA C22.2 No. 601.1 - M90 / IEC 60601-1				
Vertical displacement speed at 455 kg (1000 lb) at 230 kg (500 lb)	3 cm/sec (1.2 in/sec) 4 cm/dec (1.6 in/sec)			
Horizontal displacement speed programmable	10, 14, 16 ou 20 cm/sec; (3.9, 5.5, 6.3 ou 7.9 in/ sec) Par défaut : 16 cm/sec (6.3 in/sec)			
Battery Specifications				
Rechargeable sealed lead acid	(2X) 12VDC, 7Ah			
Side rail mounting, position anywhere, charging s	ystem			
Battery capacity with load of 91 kg / 200 lb/ 14.33 st	Up to 120 transfers			
Low battery warning indicator Visual & audible				
Charger input – 90-240 Vac, 50-60 Hz, 57-70 VA max.				
Charge indicator	Visual			
Strap Specifications				
Length	2,3 m (90.6 in)			
Automatically stops unit if twisted				
Unit Construction				
Frame – steel				
Cover – fire retardant plastic	6-a			
A				
Accessories				
a 402.15508	Charger extension - 2 m (78 in)			
b 700.00525	Scale Unit / 455 kg (1000 lb) (North America)			
b 700.00535	Scale Unit - Class III / 500 kg (1102 lb) (Europe & United Kingdom)			

11